

Conexões

Acopladores em Inox



SH

| Modelo | Tubo (mm) |
|--------|-----------|
| SH20S | 7 |
| SH30SS | 10 |
| SH40SS | 13 |



PH

| Modelo | Tubo (mm) |
|--------|-----------|
| PH20SS | 7 |
| PH30SS | 10 |
| PH40SS | 13 |



SF

| Modelo | Rosca Interna |
|--------|---------------|
| SF20SS | 1/4 |
| SF30SS | 3/8 |
| SF40SS | 1/2 |



PF

| Modelo | Rosca Interna |
|--------|---------------|
| PF20SS | 1/4 |
| PF30SS | 3/8 |
| PF40SS | 1/2 |



SM

| Modelo | Rosca Interna |
|--------|---------------|
| SM20SS | 1/4 |
| SM30SS | 3/8 |
| SM40SS | 1/2 |



PM

| Modelo | Rosca Interna |
|--------|---------------|
| PM20SS | 1/4 |
| PM30SS | 3/8 |
| PM40SS | 1/2 |



SP

| Modelo | Tubo (mm) |
|--------|-----------|
| SP20SS | 5.0 x 8.0 |
| SP30SS | 6.5 x 10 |
| SP40SS | 8.0 x 12 |



PP

| Modelo | Tubo (mm) |
|--------|-----------|
| PP20SS | 5.0 x 8.0 |
| PP30SS | 6.5 x 10 |
| PP40SS | 8.0 x 12 |

| Material | SS304 |
|---------------------|---------------|
| Fluido | Ar Comprimido |
| Rosca | BSPT |
| Pressão de Trabalho | 0 ~10 Bar |
| Temperatura | -20 ~200° C |
| Material de Vedação | Viton |